

Legend HBR Impact featuring Seastorm™ Glass

Legend HBR Impact is available in casement, casement picture, casement transom, awning, double hung and double hung picture. True Legend Impact is available in direct set and radius.

Features and Benefits

- 25-year CPVC warranty against rotting, warping, cracking or swelling
- Cellular PVC exterior with extruded clad sash
- Extruded aluminum in 22 standard colors, 20 feature colors and eight anodized finishes; custom colors also available
- Architectural trim available in a variety of CPVC casing and sill options, providing a historically accurate appearance
- Factory-applied trim details save significant time and cost
- Rough openings are identical to standard Legend windows, making it easy to mix and match on the same job
- Standard EZ Tilt operation on both the top and bottom sash; both sashes tilt in for easy cleaning
- Block and tackle balance on standard EZ Tilt is quiet, secure and operates smoothly
- Certified, proven-safe solution against hurricane blasts; laminated glass allows window to crack instead of shatter when under great pressure
- Meets and exceeds modern building codes for the coast's extreme environmental conditions
- Dampens sounds from traffic, neighbors and the outdoors
- Resistant to interior fading from constant sunlight
- Offers security against intruders with shatterproof and cutter-deterring glass

Sizes

Available in hundreds of standard and custom sizes

Glazing

- Glazed with tape and Dow Corning® 955 silicone sealant – the strongest silicone bonding agent available
- Cardinal SeaStorm™ LoE 366 insulated glass standard, featuring stainless steel spacers; tinted, tempered and laminated glass available
- Custom and special glass types available
- Insulated glass utilizes annealed glass on exterior and laminated glass on interior
- Laminated glass features PVB inner layer on units up to 26 square feet and SGP inner layer on units over 26 square feet

Exterior Trim

- Units available with WM 180 brickmould, WM 180 brickmould with flange, Williamsburg, 3-1/2" flat, 4-1/2" backband, 5-1/2" flat or plantation casing; double hung sill nose, 2" bull nose sill nose, belly sill nose, casement subsill, 2" casement subsill or half round/ellipse sill nose

Grilles

Windsor Divided Lite (WDL) = simulated divided lite

- 7/8" and 1-1/4" perimeter grille
- 7/8" and 1-1/4" stick grille
- 3/4" and 1" profiled inner grille
- 13/16" flat inner grille
- 7/8" and 1-1/4" interior wood WDL
- 7/8" and 1-1/4" exterior clad WDL
- 5/8" and 7/8" tall putty WDL
- 5/8" and 7/8" short putty WDL
- 2" tall putty simulated check rail
- 2" exterior low profile simulated check rail
- WDL aluminum clad exteriors come with stain-grade wood or CPVC for primed interiors
- Standard and custom grille patterns available

Finishes

- Interior – Available in Clear Select Pine, primed or painted white interior finishes
- Exterior – Clad products feature heavy-duty extruded aluminum cladding on sash and frame; primed products offer an assortment of traditional trim options

Clad Colors

All clad colors painted in-house with the highly durable AAMA 2604 standard finish, or upgrade to AAMA 2605 for the most challenging of environments


- 22 standard colors
- 20 feature colors; custom colors available
- 8 anodized finishes

Hardware


Available in champagne, white, bronze and black; optional finishes in faux bronze, oil rubbed bronze, satin nickel and bright brass

Performance Ratings and Certification

- For current performance ratings, visit our website at windsorwindows.com and click on "Professional Information" in the menu bar
- Performance rated to DP 50 overall; structural rating exceeds DP 50. Florida Building Commission approved; exception Dade-Broward small missile
- Visit floridabuilding.org for more information; including section details and installation



Legend HBR casement cross-section



Legend HBR double hung cross-section