

Pinnacle Sliding Patio Door

Features and Benefits

- [1]** Wood parting stops and absence of screws provide a warm, clean look
- [2]** Integral nail fin on clad doors
- [3]** Heavy-duty interlock improves air and structural performance
- [4]** Standard two-point lock for added security
- [5]** One-piece, fiberglass pultruded sill minimizes cold conduction
- [6]** Aluminum jamb covers at the head and strike jambs hide exposed screws and provide a smoother, more attractive surface
- [7]** Doors slide on two tandem, heavy-duty, end-adjustable, ball bearing rollers for years of smooth, trouble-free operation
- [8]** Improved breakaway force of panel (10 lbs) and operating force (6 lbs) provide effortless operation
- [9]** Taller sill provides excellent water performance and design pressure ratings
- [10]** Foam-backed glazing bead prevents paint and stain from bleeding
- [11]** All stiles constructed of an LVL core for a stronger, straighter, more durable door
- [12]** Panel exterior matches Pinnacle product line with consistent depth from glass to face of the panel for a clean, complementary appearance
- [13]** Panels available in traditional French or contemporary narrow stile

Sizes

- Five standard heights: 6'8", 6'10", 8'0", 9'0" and 10'0" (9'0" and 10'0" doors available in clad French slider only)
- Custom sizes available

Glazing

- Windsor Glazing System provides 3/4" double pane insulated glass; Cardinal® LoE 366 glass standard; tinted, tempered, obscure and laminated glass available
- Interior stop glazed with silicone sealant
- Custom and special glass types available

Exterior Trim

- Clad doors available with WM 180 brickmould, Williamsburg or 3-1/2" flat casing; primed doors available with WM 180 brickmould, WM 180 brickmould with flange, Williamsburg, 3-1/2" flat, 4-1/2" backband, 5-1/2" flat or plantation casing

Grilles

Windsor Divided Lite (WDL) = simulated divided lite

- 7/8" and 1-1/4" Perimeter Grille (*NOT available on radius doors*)
- 7/8" and 1-1/4" Stick Grille (*Radius swing doors only*)
- 3-4" and 1" Profiled Inner Grille
- 13/16" Flat Inner Grille
- 7/8" and 1-1/4" Ogee WDL
- 5/8", 7/8", 1-1/4" and 2" Short Putty WDL
- 5/8", 7/8", 1-1/4" and 2" Short Contemporary WDL
- 3-3/8" Simulated Mid Rail
- Standard and custom grille patterns available

Finishes

- Interior – Clad doors available in Clear Select Pine, Douglas Fir, Natural Alder, primed, painted white or painted black interior finishes; primed doors available in Clear Select Pine, primed or painted white interior finishes
- Exterior – Clad doors available in heavy-duty extruded aluminum cladding; primed doors offer an assortment of traditional trim options

Weatherstripping

- Flexible, weatherable PVC and foam seal at the head and jambs with a pile fin-seal weatherstripping at the interlocks; pile weatherstripping also used at the bottom of the operating panel and at the ends of the interlock

Clad Colors

All clad colors painted in-house with the highly durable AAMA 2604 standard finish, or upgrade to AAMA 2605 for the most challenging of environments

- 22 standard colors
- 21 feature colors; custom colors available
- 8 anodized finishes

Hardware

- Contemporary or Euro handle available in white, brushed chrome, polished chrome, satin nickel, antique nickel, brass*, antique brass*, faux bronze, oil rubbed bronze and black
- Flush mount handle available in satin nickel, faux bronze, black matte and oil rubbed bronze

Performance Ratings

For current performance ratings, visit our website at windsorwindows.com and click on "Professional Information" in the menu bar

