



Pinnacle Select Lift & Slide Patio Doors

Features and Benefits

- Available in aluminum exterior / wood interior, or aluminum exterior / aluminum interior
- Thermally broken aluminum panels and frames
- Stacking lift & slide system aligns all panels with the stationary panel when in the fully open position; all panels are visible
- Pocket lift & slide system incorporates a pocket into the wall cavity to conceal all panels when they are in the fully open position
- Door jamb widths vary depending on the number of panels in the lift & slide door system and the handing
- Up to five panels in any one direction and 10 panels for a bi-parting lift & slide door
- 2-3/8" thick panel construction
- Narrow 3-3/16" wide panels reveal more glass for beautiful views
- Standard and recessed sill options
- Two 2-wheel carriages engineered to provide maximum support
- Nylon rollers combined with stainless steel ball bearings provide effortless operation
- Multi-point locking system
- Lead panel on pocket doors come with a finger pull

Sizes

- Standard panel widths: 3-0, 4-0, 5-0, 6-0
- Standard panel heights: 8-0, 9-0, 10-0, 11-0, 12-0
- Maximum panel size: 5-0 x 12-0 and 6-0 x 10-0

Glazing

- 1" overall double pane insulated glass, Cardinal® LoE 366 glass standard, LoE 270 and Dual Low-E optional
- Interior stop glazed

Finishes

- Interior – Wood interior doors available in Clear Select Pine or Douglas Fir (Note: interior prefinish not available); aluminum interior doors available in color matched aluminum (Note: exterior and interior aluminum colors will be the same)
- Exterior – All doors have heavy-duty thermally broken aluminum panels and frames

Clad Colors

All clad colors painted in-house with the highly durable AAMA 2604 standard finish or upgrade to AAMA 2605 for the most challenging of environments

- 24 Standard Clad Colors available in 2604 and 2605 finish
- 20 Feature Clad Colors available in 2604 and 2605 finish (Custom color matching is also available)
- 7 Matte Clad Colors available in the 2604 finish only

Hardware

- Two 2-wheel carriages engineered to provide maximum support
- Nylon rollers combined with stainless steel ball bearings provide effortless operation
- Multi-point locking system
- Designed to support up to 880 lb panels
- Finger pull on pocket door lead panels



Lift & Slide 1-1/8" standard sill



Lift & Slide 2-1/2" recessed sill with drainage



Lift & Slide Alum Ext. Wood Int. Panel



Lift & Slide Alum Ext. Alum Int. Panel



Lift & Slide 2-1/2" recessed sill no drainage