



# Pinnacle Select Lift & Slide Patio Doors

## Features and Benefits

- Available in aluminum exterior / wood interior, or aluminum exterior / aluminum interior
- Thermally broken aluminum panels and frames
- Stacking lift & slide system aligns all panels with the stationary panel when in the fully open position; all panels are visible
- Pocket lift & slide system incorporates a pocket into the wall cavity to conceal all panels when they are in the fully open position
- Door jamb widths vary depending on the number of panels in the lift & slide door system and the handing
- Up to five panels in any one direction and 10 panels for a bi-parting lift & slide door
- 2-3/8" thick panel construction
- Narrow 3-3/16" wide panels reveal more glass for beautiful views
- Standard and recessed sill options
- Two 2-wheel carriages engineered to provide maximum support
- Nylon rollers combined with stainless steel ball bearings provide effortless operation
- Multi-point locking system
- Lead panel on pocket doors come with a finger pull

## Sizes

- Standard panel widths: 3-0, 4-0, 5-0, 6-0
- Standard panel heights: 8-0, 9-0, 10-0, 11-0, 12-0
- Maximum panel size: 5-0 x 12-0 and 6-0 x 10-0

## Glazing

- 1" overall double pane insulated glass, Cardinal® LoE 366 glass standard, LoE 270 and Dual Low-E optional
- Interior stop glazed

## Finishes

- Interior – Wood interior doors available in Clear Select Pine or Douglas Fir; aluminum interior doors available in color matched aluminum
- Exterior – All doors have heavy-duty thermally broken aluminum panels and frames

## Clad Colors

All clad colors painted with the highly durability of AAMA 2604 standard finish, or upgrade to AAMA 2605 for the most challenging of environments

- 23 Standard Clad Colors available in 2604 and 2605 finish
- 20 Feature Clad Colors available in 2604 and 2605 finish
- 7 Matte Clad Colors available in 2604 finish only

## Hardware

- Two 2-wheel carriages engineered to provide maximum support
- Nylon rollers combined with stainless steel ball bearings provide effortless operation
- Multi-point locking system
- Designed to support up to 880 lb panels
- Finger pull on pocket door lead panels



Lift & Slide 1-1/8" standard sill



Lift & Slide 2-1/2" recessed sill with drainage



Lift & Slide Alum Ext. Wood Int. Panel



Lift & Slide Alum Ext. Alum Int. Panel



Lift & Slide 2-1/2" recessed sill no drainage