

Pinnacle Select Lift & Slide Patio Doors

Features and Benefits

- Available in aluminum exterior / wood interior, or aluminum exterior / aluminum interior
- Thermally broken aluminum panels and frames
- Stacking lift & slide system aligns all panels with the stationary panel when in the fully open position; all panels are visible
- Pocket lift & slide system incorporates a pocket into the wall cavity to conceal all panels when they are in the fully open position
- Door jamb widths vary depending on the number of panels in the lift & slide door system and the handing
- Up to five panels in any one direction and 10 panels for a bi-parting lift & slide door
- 2-3/8" thick panel construction
- Narrow 3-3/16" wide panels reveal more glass for beautiful views
- Standard and recessed sill options
- Two 2-wheel carriages engineered to provide maximum support
- Nylon rollers combined with stainless steel ball bearings provide effortless operation
- Multi-point locking system
- Lead panel on pocket doors come with a finger pull

Sizes

- Standard panel widths: 3-0, 4-0, 5-0, 6-0
- Standard panel heights: 8-0, 9-0, 10-0, 11-0, 12-0
- Maximum panel size: 5-0 x 12-0 and 6-0 x 10-0

Glazing

- 1" overall double pane insulated glass, Cardinal® LoE 366 glass standard, LoE 270 and Dual Low-E optional
- Interior stop glazed

Finishes

- Interior Wood interior doors available in Clear Select Pine or Douglas Fir (Note: interior prefinish not available); aluminum interior doors available in color matched aluminum (Note: exterior and interior aluminum colors will be the same)
- Exterior All doors have heavy-duty thermally broken aluminum panels and frames

Clad Colors

All clad colors painted with the highly durability of AAMA 2604 standard finish, or upgrade to AAMA 2605 for the most challenging of environments

- 24 Standard Clad Colors available in 2604 and 2605 finish
- 20 Feature Clad Colors available in 2604 and 2605 finish
- 7 Matte Clad Colors available in 2604 finish only



Lift & Slide Alum Ext. Alum Int. Panel

Hardware

- Two 2-wheel carriages engineered to provide maximum support
- Nylon rollers combined with stainless steel ball bearings provide effortless operation
- Multi-point locking system
- Designed to support up to 880 lb panels
- Finger pull on pocket door lead panels



Lift & Slide 1-1/8" standard sill



Lift & Slide 2-1/2" recessed sill with drainage



Lift & Slide 2-1/2" recessed sill no drainage



Lift & Slide Alum Ext. Wood Int. Panel