

Pinnacle Series

GLIDE-BY

ELEVATIONS

SCALE: 1/8" = 1'-0"

Mas. Opg. Clad Rough Opg. Frame Glass							
	36 3/4	42 3/4	48 3/4	54 3/4	60 3/4	66 3/4	72 3/4
	36 3/4	42 3/4	48 3/4	54 3/4	60 3/4	66 3/4	72 3/4
	36	42	48	54	60	66	72
	14 7/8	17 7/8	20 7/8	23 7/8	26 7/8	29 7/8	32 7/8
24 1/2							
24 1/2	3624	4224	4824	5424	6024	6624	7224
30 1/2							
30 1/2	3630	4230	4830	5430	6030	6630	7230
36 1/2							
36 1/2	3636	4236	4836	5436	6036	6636	7236
42 1/2							
42 1/2	3642	4242	4842	5442	6042	6642	7242
48 1/2							
48 1/2	3648	4248	4848	5448	6048	6648	7248
54 1/2							
54 1/2	3654	4254	4854	5454	6054	6654	7254
60 1/2							
60 1/2	3660	4260	4860	5460	6060	6660	7260

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD

- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG

- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR CLAD 3 1/2" FLAT CASING

- ADD 5 7/8" TO FRAME WIDTH
- ADD 3 5/16" TO FRAME HEIGHT*


* ADD ADDITIONAL 7/8" FOR 1 1/4" SUBSILL
ADD ADDITIONAL 1 7/8" FOR 2 1/4" SUBSILL

NOTE:
ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING

OTHER GRILLE PATTERNS



HANDING










NOTES:
CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
SHADED SIZES MEET MOST EGRESS REQUIREMENTS. VERIFY LOCAL CODES.

Pinnacle Series

GLIDE-BY - TRIPLES

ELEVATIONS

SCALE: 1/8" = 1'-0"

Mas. Opg. Clad Rough Opg. Frame Glass	72 3/4 72 3/4 72 14 7/8-35-14 7/8	84 3/4 84 3/4 84 17 7/8-41-17 7/8	96 3/4 96 3/4 96 20 7/8-47-20 7/8	108 3/4 108 3/4 108 23 7/8-53-23 7/8
24 1/2 24 1/2 24 18 1/2	 7224	 8424	 9624	 10824
30 1/2 30 1/2 30 24 1/2	 7230	 8430	 9630	 10830
36 1/2 36 1/2 36 30 1/2	 7236	 8436	 9636	 10836
42 1/2 42 1/2 42 36 1/2	 7242	 8442	 9642	 10842
48 1/2 48 1/2 48 42 1/2	 7248	 8448	 9648	 10848
54 1/2 54 1/2 54 48 1/2	 7254	 8442	 9654	 10854
60 1/2 60 1/2 60 54 1/2	 7260	 8460	 9660	 10860

UNIT SIZE INFORMATION

FOR CLAD BRICKMOULD

- ADD 2 13/16" TO FRAME WIDTH
- ADD 1 3/4" TO FRAME HEIGHT*

FOR CLAD WILLIAMSBURG

- ADD 6 1/2" TO FRAME WIDTH
- ADD 3 5/8" TO FRAME HEIGHT*

FOR CLAD 3 1/2" FLAT CASING


- ADD 5 7/8" TO FRAME WIDTH
- ADD 3 5/16" TO FRAME HEIGHT*

* ADD ADDITIONAL 7/8" FOR 1 1/4" SUBSILL
ADD ADDITIONAL 1 7/8" FOR 2 1/4" SUBSILL


NOTE:

ADD 3/4" TO UNIT WIDTH & 1/2" TO UNIT HEIGHT
TO CALCULATE MASONRY OPENING


OTHER GRILLE PATTERNS




PRAIRIE




DIAMOND



SINGLE
PLAZA




DOUBLE
PLAZA



TRIPLE
PLAZA

HANDING



XOX

NOTES:

CLAD MASONRY OPENINGS ARE FOR STANDARD FRAME WITH NO CASING.
SHADED SIZES MEET MOST EGRESS REQUIREMENTS. VERIFY LOCAL CODES.